

AMENDMENTS TO THE SPECIFICATION

Please amend page 12, paragraph 3 as follows:

In the preferred three-dimensional configuration of schoolhouse 20, interior storage space 36 preferably includes relevant ornamentation. That is, inner surfaces 26d, 28d, 30d and/or 32d preferably depict a school room. Preferably, clock 40 and chalk board 42 ~~(not shown)~~ are provided in working form, to facilitate the enjoyable use of schoolhouse 20 as a toy or doll house when not being utilized for storage, wherein clock 40 preferably has movable hands 44a and chalk board 42 possesses a writeable surface. It is anticipated that other forms of ornamentation could be utilized within schoolhouse 20 such as, for exemplary purposes only, an ABC chart and/or magnetic, dry erase board. Further, in an alternate three-dimensional configuration, such as a domed stadium, ornamentation could depict a locker room and/or playing field.

Please amend page 13, paragraph 2 as follows:

Preferably, front wall 26 has two windows 50a and 50b defined therein; first side wall 28 has five windows 52a, 52b, 52c, 52d and 52e defined therein; and second side wall 32 has five windows 54a, 54b, 54c, 54d and 54e ~~(54d and 54e not shown)~~ defined therein, preferably resulting in a total of twelve windows. Each window 50a-50b, 52a-52e, and 54a-54e preferably functions as a picture frame that is dimensioned to receive and display a photograph. A total of

twelve windows is preferred to enable the placement and display of twelve pictures, preferably one corresponding to each school year, first grade through twelfth grade. Although twelve is the preferred number of windows, any appropriate number could be alternately utilized. For example, additional windows could be included in order to facilitate the inclusion and display of kindergarten and/or preschool photos.

Please amend page 14, paragraph 2 as follows:

Preferably, accessways 60a and 60b are defined in top edge 26b of front wall 26; accessways 60c-60g are defined in top edge 28a of first side wall 28; and accessways 60h-60l are defined in top edge 32b of second side wall 32. Each preferred accessway 60a-60l is preferably relatedly positioned to each window 50a-50b, 52a-52e, and 54a-54e, respectively, to enable slidable insertion of a photograph into same, as best seen in FIG. 3. In an alternate configuration, as depicted in FIG. 4, front wall 26, first side wall 28 and second side wall 32 could be formed without accessways 60a-60l defined therein. Instead, photo support members ~~62a-62b~~ (not shown) could be provided on inner surface 26d of front wall 26, photo support members such as 62~~ee~~ee-62g ~~(62c-62d not shown)~~ could be provided on inner surface 28d of first side wall 28, and photo support members such as 62h-62~~j~~j ~~(62k-62l not shown)~~ could be provided on inner surface 32d of second side wall 32.